

## **E07 – Easy Move - Lifting Platform Technical Data**

Lifting system for a person with limited locomotory capacity

### **Approval**

- TÜV approval for the safety gear;
- TÜV approval for the locks;
- In conformity with the European Directive 2006/95 on Low Voltage;
- In conformity with the European Directive 2004/108 on Electromagnetic Compatibility;
- In conformity with the European Directive 2006/42 Machinery Directive (certificate of conformity issued by IMQ).

### **Installation**

The system can be installed either indoors or outdoors. The power pack and the electrical system must always be housed in a special protected shaft comprising the motor cabinet supplied as standard. If the power pack can reach temperatures below 0°C, it is mandatory to equip the hydraulic system with oil heating to be ordered separately. For outdoor installations the guards must have a roof. The hydraulic hose reaches the feet of the guides, with a standard length of 3 m. (6 or 9 m. max on request).

**Working load:** up to 400 kg.

<b>E07 Easy Move</b>	<b>Kg</b>
Cabin with Color, Wood, Steel, Inox series walls	400
Cabin with Glass series walls	350
N°1 Cabin door + Color, Wood, Steel, Inox series walls	300
N°1 Cabin door + N° 1 Glass series wall	250
N°1 Cabin door + N° 2 Glass series walls	250

**Travel:** 13 metres.

**Headroom:** 2270 mm; 2410 mm in case of cabin door.

**Intermediate stops:** max 3 with a minimum distance between the stops of 230 mm.

## Motor and electric supply

Motor located in the hydraulic power pack with the following specifications:

- Power 1.8 kW;
- Mains voltage: 230V-mono;
- Motor power supply voltage: 230V;
- Auxiliary power supply voltage: 24V;

## Fastenings

At the customer's choice, with pre-mounted wall anchoring brackets or alternatively with back wall with mechanical anchors, with back wall with chemical anchors or with vertical I-beam; if optional, with metal frame.

## Guides

Machined T70-1a sections.

## Cabin materials and colours

The cabin is supplied as standard with: "Beige" type "Color" series walls, "Grey Rubber" type platform floor covering, the doors and the self-supporting structure if opted for will be RAL 9023 pearly dark grey; other materials and colours are available both as regards the walls (3 clad plates in the "color" series and 1 simil-inox (grey) "color" series, 2 simil-inox "wood" series, 2 simil-inox "marble" series, 2 glass "glass" series, 2 stainless steel "inox" series, 3 clad steel in "steel" series) and for the floors (2 imitation-wood, 4 non-slip safe-step) and for the alternative colours of doors and self-supporting structure (2).

## Cabin

Composed of 3 physical walls made of the above-mentioned materials of clad steel; the fourth cabin side, or any side that is free of walls, will be equipped with an infrared barrier able to intercept any obstacle larger than 1 cm<sup>2</sup>; the surface of the platform is covered with Rubber. The on-board push-button panel supplied as standard is horizontal, equipped with a telephone dial pad and fitted for an I-button, the roof is the four spot type.

On request in the cabin: handle in the "rich" series (brushed aluminium), horizontal and vertical mirror, alternative vertical pushbutton panel with autodialer, LCD display on board and on the floor, telephone dial pad, I-button; alternative horizontal pushbutton panel with autodialer, "starry sky", "labyrinth" or "LED spotlights" type alternative roofs, ambient music, remote floor controls.

The overall dimensions\* of the platform for those supplied as standard are: 850x900, 850x1250, 900x850, 950x770, 1000x1250, 1000x1400, 1100x1400, 1250x1000, 1250x1250, 1250x850, 1400x1000, 1400x1100, 1400x1200. (\*to obtain the working dimensions, 30 mm for each on-board wall and 10 mm for each infrared barrier should be taken off; in case of cabin on-board folding door, the additional platform overall dimension is 100 mm).

Special platform sizes are also available on request, provided that the surface is max 1.55 m<sup>2</sup>. and no side of the platform exceeds a useful length of 1400 mm.

**Transmission:** with hydraulic cylinder and double cable.

**Max speed:** 0.15 m/sec;

### **Controls**

On board push-button panel with dead-man's controls, size 50x50 mm, with Braille indications and blue backlighting (unless there is a cabin door combined with 3 walls, in which case operation will be by universal manoeuvre); floor push-buttons with universal manoeuvre operation, size 50x50, vandal-proof with Braille indications and red and green backlighting for signalling respectively product in use/occupied and product free/available for use; all the controls work only if the doors are closed.

### **Electrical safety devices**

On-board emergency push-button connected with an audible alarm and pre-set numbers (at the customer's choice), integrated with a telephone device; thermal circuit breaker on the motor; landing limit switch; over-run microswitch; pit and headroom under safety microswitches that inhibit the controls in the cabin and on the floor when activated; cable slackening/breaking safety device; auxiliary circuit and supply circuit in separate cables; electric driving locks approved according to the EEC Directive 81/2, with safety microswitch for approved door release control; automatic levelling at the floor (upper, lower and intermediate) within + / - 20 mm with door open and closed; on-board anti-blackout descent; on-board emergency light; display of floor reached on the display on the lifting platform and at the floor; timed cabin lights, timed descent.

### **Mechanical safety devices**

Two lifting cables with spring system for load division; safety gear for lifts (type approved according to the EEC directives 84/529 and 86/312) that acts on the guides; protection at the floors with landing doors; emergency door release from the outside, with special key; artificial pit of 500 mm under safety microswitch, artificial headroom of 300mm under safety microswitch; load-bearing cabin roof.

### **Hydraulic safety devices**

Down speed control valve; safety gear valve integrated in the cylinder; check valve; pressure relief valve on the hydraulic circuit; emergency descent from floor level; hand pump and pressure switch.

### **Doors**

Panoramic aluminium with laminated glass, motorized panoramic double-hinged with laminated glass, partitioned with window or panoramic (with laminated glass

available only for sizes 800, 860, 900); cabin automatic stainless steel folding door of sizes 650, 750, 800 (max. 1).

The standard supply features doors with one leaf, manual movement (the retracting mechanical actuators make them semiautomatic therefore with independent closure); For the doors with one leaf the motorization is available on request. The double leaf door is always motorized.

### **Guard**

When there is a metal frame the roof for indoor or outdoor use can be ordered on request (mandatory for outdoor installations).

**Pit:** 120 mm for masonry shaft and aluminium guards; 140 mm for metal framework.

**Cabin height:** 2000 mm

### **State of supply**

In components to be assembled.

If there is a metal frame there will be sectional steel profiles with laminated glass or laminated sheet plate blind panels.

### **At the customer's charge**

The customer must pay for and make all necessary changes to the shaft before delivery but to our design.

In addition, the customer is to pay the expenses related to the construction of the dedicated electric line to our panel, with conductors of minimum cross-section 2.5 mm<sup>2</sup>, which can be disconnected with a residual current circuit breaker of nominal capacity 16A and sensitivity 0.03A and earthed with a cable of 2.5 mm<sup>2</sup>, to supply the machine.

Again, the customer is to pay for the construction of a separate electric line to the one described, with conductors of minimum cross-section 2.5 mm<sup>2</sup>, which can be disconnected with a residual current circuit breaker of nominal capacity 16A and sensitivity 0.03A and earthed with a cable of 2.5 mm<sup>2</sup>. This line must have one or more 16A service power sockets for maintenance, of which at least one located in the artificial pit of the travel shaft.

At customer's care and charge is also the setting up of a line with conductors of 1.5 mm<sup>2</sup> with circuit breaker of nominal capacity 10A and sensitivity 0.03A, earthed with a cable of 1.5 mm<sup>2</sup> to supply the cabin lights.

Lastly, it is at customer's care and charge the setting up of a telephone line through a special cable next to the electric panel.

The responsibility for the strength of the walls, terraces, floors and plinths is entirely to the charge of the customer.

### **N.B. The data given herein are indicative and not binding;**

**Vimec S.r.l. reserves the right to make any changes that it may consider appropriate at any time and with no obligation to give any advance notice thereof.**

**01/11/2011**